

Pengaruh Temperatur dan Prosentase Magnesium terhadap Karakteristik Komposit Matrik Logam Al/AL₂O₃ hasil Infiltrasi Tanpa Tekanan

Anne Zulfia, author

Deskripsi Lengkap: <https://lib.ui.ac.id/detail?id=20304683&lokasi=lokal>

Abstrak

Metal Matrix Composite (MMCs) is combination from two material or more with metal as matrix developed to improve the nature of metal; strength, hardness. electric resistance stability at high temperature. Aluminum as a matrix composite developed because is light, cheap, and easy to fabrication. Pressureless infiltration is one of the fabrication process of metal matrix composite in a melt condition which is developing because more economic; no need complicated equipments. Characteristic of metal matrix: composite can be influenced by infiltration temperature, dopant content (Magnesium), % Vf reinforcement and holding time. This research aim is to study the effect of temperature infiltration, as well as magnesium content on characterization of Al₂O₃, metal matrix composite i.e, thermal expansion, hardness, wear resistance, porosity and density as well as metallography. The infiltration temperature used various from 800 to 1200°C and Al₂O₃ particle reinforcement was 5U%Fj= The magnesium content was also various from 4% to 12% wt and holding time was 10 hours. The results shows that higher magnesium content produced more Al molten infiltrated into Al₂O₃ preform. It is found that the optimum performance of composite produced at 1100° C.