

# Pengaruh material homogen dan inhomogen dalam evaluasi gamma index teknik IMRT (Intensity Modulated Radiotherapy) berdasarkan citra pasien fan beam dan cone beam CT = Homogeneous and inhomogenous material effect in gamma index evaluation of IMRT technique based on beam and cone beam CT patient image

Wahyu Edy Wibowo, author

Deskripsi Lengkap: <https://lib.ui.ac.id/detail?id=20422727&lokasi=lokal>

---

## Abstrak

[Telah dilakukan penelitian dalam mengevaluasi pengaruh material homogen dan inhomogen pada teknik IMRT (Intensity Modulated Radiotherapy) menggunakan modalitas Fan Beam CT (FBCT) dan Cone Beam CT (CBCT) terhadap Gamma Index (GI). Perencanaan ulang dilakukan untuk 5 pasien kanker paru kanan pada modalitas FBCT dan CBCT menggunakan TPS Phillips Pinnacle energi foton 6 MV. Menggunakan Teknik IMRT 30 segmen, 50 segmen, dan 70 segmen untuk perencanaan terapi. Calculation Grid Resolution (CGR) 0.2 cm dan 0.4 cm digunakan sebagai resolusi dalam perhitungan dosis. Serta kalibrasi bilangan CT (KBC) FBCT, CBCT, dan linear dipergunakan sebagai koreksi CT density number. Pengukuran planar dose untuk evaluasi Gamma Index (DD 2% / DTA 2 mm, passing rate 90%) dilakukan pada SAD 100 cm dengan material homogen dan inhomogen pada kedalaman 1.5 cm, 5 cm, dan 10 cm. Didapatkan deviasi nilai rata-rata GI antara CGR 0.2 cm dengan 0.4 cm material homogen modalitas FBCT dan CBCT berturut-turut 1.46% dan 1.13%. Serta deviasi pada material inhomogen sebesar 2.54% (FBCT) dan 1.74% (CBCT). Deviasi Nilai rata-rata GI antara FBCT dengan CBCT dengan CGR 0.2 cm berturut-turut 1.95% (homogen) dan 2.36% (inhomogen). Dan deviasi Nilai rata-rata GI antara material homogen dan material ekuivalen homogen sebesar 0.80%. Dari hasil penelitian yang didapat, bahwa evaluasi Gamma Index dapat dipengaruhi oleh jumlah segmen, modalitas CT, kalibrasi bilangan CT, Calculation Grid Resolution, dan kedalaman material.

.....These Studies have been carried out to evaluate the effect of a homogeneous and inhomogeneous material on IMRT Technique (Intensity Modulated Radiotherapy) using Fan Beam CT (FBCT) and Cone Beam CT (CBCT) for the Gamma Index (GI). The Phillips Pinnacle treatment plan was used to replan 5 patients on right side of lung cancer. Photon 6 MV was applied to this technique with 30 segments, 50 segments, and 70 segments, respectively. Using Calculation Grid Resolution (CGR) 0.2 cm and 0.4 cm for resolution in the calculation of the dose. As well as the calibration of CT numbers (CCN) FBCT, CBCT, and the linear density are used as a correction CT number. The planar measurement for the evaluation of Gamma Index (DD 2% / DTA 2 mm, the passing rate of 90%) carried out at 100 cm SAD with the homogeneous and inhomogeneous material at a depth of 1.5 cm, 5 cm, and 10 cm, respectively. We obtained deviation average value of GI between CGR 0.2 cm and 0.4 cm using the homogeneous material on FBCT and CBCT modality 1.46% and 1:13%, respectively. As well as the material inhomogeneous deviation of 2.54% (FBCT) and 1.74% (CBCT). The deviation of the average GI value between FBCT with CBCT with CGR 0.2 cm respectively 1.95% (homogeneous) and 2.36% (inhomogeneous). Finally, the deviation of the average GI value between homogeneous and equivalent of homogeneous material is 0.80%. From the results obtained, that the Gamma Index can be influenced by the number of segments, modalities of CT, calibration of CT numbers, calculation grid resolution and depth of material.

, These  
Studies  
have  
been  
carried  
out  
to  
evaluate  
the  
effect  
of  
a  
homogeneous  
and  
inhomogeneous  
material  
on  
IMRT  
Technique  
(Intensity  
Modulated  
Radiotherapy)  
using  
Fan  
Beam  
CT  
(FBCT)  
and  
Cone  
Beam  
CT  
(CBCT)  
for  
the  
Gamma  
Index  
(GI).  
The  
Phillips

Pinnacle  
treatment  
plan  
was  
used  
to  
replan  
5  
patients  
on  
right  
side  
of  
lung  
cancer.

Photon  
6  
MV  
was  
applied  
to  
this  
technique  
with  
30  
segments,  
50  
segments,  
and  
70  
segments,  
repectively.

Using  
Calculation  
Grid  
Resolution  
(CGR)  
0.2  
cm  
and  
0.4  
cm

for  
resolution  
in  
the  
calculation  
of  
the  
dose.

As  
well  
as  
the  
calibration  
of  
CT  
numbers  
(CCN)  
FBCT,  
CBCT,  
and  
the  
linear  
density  
are  
used  
as  
a  
correction  
CT  
number.

The  
planar  
measurement  
for  
the  
evaluation  
of  
Gamma  
Index  
(DD  
2%  
/

DTA  
2  
mm,  
the  
passing  
rate  
of  
90%)  
carried  
out  
at  
100  
cm  
SAD  
with  
the  
homogeneous  
and  
inhomogeneous  
material  
at  
a  
depth  
of  
1.5  
cm,  
5  
cm,  
and  
10  
cm,  
respectively.  
We  
obtained  
deviation  
average  
value  
of  
GI  
between  
CGR  
0.2

cm  
and  
0.4  
cm  
using  
the  
homogeneous  
material  
on  
FBCT  
and  
CBCT  
modality  
&#8804;1.46%  
and  
&#8804;  
1:13%,  
respectively.

As  
well  
as  
the  
material  
inhomogeneous  
deviation  
of  
&#8804;  
2.54%  
(FBCT)  
and  
&#8804;  
1.74%  
(CBCT).

The  
deviation  
of  
the  
average  
GI  
value  
between  
FBCT

with  
CBCT  
with  
CGR  
0.2  
cm  
respectively  
&#8804;  
1.95%  
(homogeneous)  
and  
&#8804;  
2.36%  
(inhomogeneous).

Finally,  
the  
deviation  
of  
the  
average  
GI  
value  
between  
homogeneous  
and  
equivalent  
of  
homogeneous  
material  
is  
&#8804;  
0.80%.

From  
the  
results  
obtained,  
that  
the  
Gamma  
Index  
can  
be

influenced  
by  
the  
number  
of  
segments,  
modalities  
of  
CT,  
calibration  
of  
CT  
numbers,  
calculation  
grid  
resolution  
and  
depth  
of  
material.

Key  
words  
:  
Calculation  
Grid  
Resolution,  
Calibration  
of  
CT  
Numbers,  
Cone]