

Analisis risiko pada pipa bawah laut 16" main oil line mol epro - ekom di Laut Jawa tahun 2016 = Risk analysis of subsea pipeline 16" main oil line mol epro ekom located at Java Sea in 2016

Firmansyah, author

Deskripsi Lengkap: <https://lib.ui.ac.id/detail?id=20433049&lokasi=lokal>

Abstrak

Analisis risiko pada pipa bawah laut 16" Main Oil Line EFPRO - EKOM di Laut Jawa ini dilakukan mengingat adanya potensi bahaya dan risiko tumpahan minyak sehingga dapat berdampak pada ekosistem laut disekitar operasi kerja. Penelitian ini bersifat deskriptif analitik dan dilakukan dengan metode semi kuantitatif. Model yang digunakan dalam penelitian ini adalah model penilaian risiko yang dikembangkan oleh Kent Muhlbauer (2004) dalam bukunya Pipeline Risk Management.

Tujuan dari penelitian ini adalah untuk mendapatkan tingkat risiko relatif sehingga didapatkan gambaran risiko yang berguna bagi manajemen dalam mengambil keputusan guna mencegah kejadian kecelakaan yang diakibatkan kegagalan pipa.

Hasil dari penelitian ini menunjukkan bahwa pada pipa sepanjang 32.14 km tersebut memiliki nilai rata-rata untuk Design Index sebesar (59.13), Corrosion Index (68.16), Third-party Damage Index (72) dan Incorrect Operations Index (82). Sedangkan nilai risiko relatif tertinggi adalah pada Kilometer Post (KP) 0-1 jalur pipa.

<hr><i>Risk analysis of subsea pipeline 16" Main Oil Line (MOL) EFPRO - EKOM located at Java Sea was conducted because of the potential hazards and the risk of oil spills that possible impact on ecosystems around the work operations. This research is descriptive analytic and performed by semi-quantitative method. The model used in this study is a model of risk assessment developed by Kent Muhlbauer (2004) in his book ?Pipeline Risk Management.

The purpose of this study was to obtain relative risk that are useful to management in making decisions in order to prevent the occurrence of accidents which caused by the failure of the pipe.

The results of this study showed that the pipeline along the 32.14 km has an average value for the Design Index (59.13), Corrosion Index (68.16), Third party Damage Index (72) and Incorrect Operations Index (82). While the value of the highest relative risk was at Kilometre Post (KP) 0-1 pipeline.</i>