

## Improvement of carbon dioxide capture using graphite waste/ fe<sub>3</sub>o<sub>4</sub> composites

Eny Kusrini, author

Deskripsi Lengkap: <https://lib.ui.ac.id/detail?id=9999920530827&lokasi=lokal>

---

### Abstrak

The abundance of graphite waste can be processed into valuable materials; one alternative is by making it into an adsorbent. Graphite-based adsorbent modification can be accomplished by adding magnetite nanoparticles Fe<sub>3</sub>O<sub>4</sub>. The addition of magnetite nanoparticles has been reported to improve the adsorption ability of the graphite waste. In this study, we have developed a new carbon dioxide (CO<sub>2</sub>) adsorbent based on graphite waste modified with magnetite nanoparticle Fe<sub>3</sub>O<sub>4</sub>. The Fe<sub>3</sub>O<sub>4</sub> were prepared using an impregnation technique. The graphite/Fe<sub>3</sub>O<sub>4</sub> composites were characterized by scanning electron microscopy with an energy-dispersive X-ray system (SEM-EDX) and Brunauer, Emmett, and Teller (BET). The CO<sub>2</sub> adsorption performance was evaluated using an isothermal adsorption method at various temperatures (30, 35, and 45°C) and pressures (3, 5, 8, 15, and 20 bar). This resulted in graphite with different magnetite modification levels, namely non-modified graphite (GNM), a graphite/Fe<sub>3</sub>O<sub>4</sub> 20% (w/w) composite (G/Fe<sub>3</sub>O<sub>4</sub> 20%), and a graphite/Fe<sub>3</sub>O<sub>4</sub> 35% (w/w) (G/Fe<sub>3</sub>O<sub>4</sub> 35%), which indicated that the largest adsorption capacity is 10.305 mmol.g<sup>-1</sup> at 30°C and 20 bar pressure for the G/Fe<sub>3</sub>O<sub>4</sub> 20% composite. This finding further revealed that modifying graphite waste with magnetite nanoparticles Fe<sub>3</sub>O<sub>4</sub> has been proved to increase the capacity for adsorbing CO<sub>2</sub> gas.