

**DAFTAR PUSTAKA**

- Aytekin, M. (1997). *Numerical Modeling of EPS Geofom used with Swelling Soil, Geotextile and Geomembrane*, 15(1997), pp.133-146.
- Bernal, A. (1996). *Laboratory Study on The Use of Tire Shreds and Rubber Sand in Backfills and Reinforced Soil Applications*. PhD Thesis. Purdue University, 1996.
- Cecich, V., Gonzales, L., Hoisaeter, A., Williams, J. and Reddy K. 1996. *Use of Shredded Tires as Lightweight Backfill Material for Retaining Structures. Waste Management and Research*, (1996)14, pp.433-451.
- Expanded Shale, Clay and Slate Institute.(1994). *Introducing the Friendly Material: Rotary Kiln Produced Lightweight Soil Conditioner Introducing the Friendly*, Salt Lake City, Reprinted August 2002.
- Ghani, A.N.A., Ahmad, F., and Hamir, R. (2002). *Varying Effect of Compressible Layers in Retaining Wall Backfill*. In Proceedings of 2nd World Engineering Congress. (B.B.K. Huat et. al, ed.), Selangor: UPM Press, 2002. pp. 114-116
- .(2003). *Shredded Tire Based Geocomposite As Drainage And Load Reduction Layers For Earth Retaining Structures*, PhD Candidate School of Civil Engineering Universiti Sains Malaysia.
- Horvath, J.S. (1997). *The Compressible Inclusion function of EPS Geofom. Geotextile and Geomembrane*, 15(1997), pp.77-120.
- Humphrey, D.N., Whetten, N., Weaver, J., Recker, K., and Cosgrove, T.A. (1998). *Tire Shreds as Lightweight Fill for Embankments and Retaining Walls*. In Proc. of Geo- Congress, ASCE Geotech. Spec. Publ. No.79, 1998.: ASCE. pp.51-65.
- Lee, J.H., Salgado, R., Bernal, A., and Lovell, C.W. (1999). *Shredded Tires and Rubber Sand as Lightweight Backfill*. *ASCE J. Geotech. and Geoenv. Enrg.*, Vol. 125, No.2, Feb. 1999, pp.132-141.
- Martin Ginster dan Ratale H. matjie.(1947). *Benefical Utilisation of Sasol Coal Gasification Ash*, Sasolburg.



Murphy, G.P. (1998). *The Influence of Geofom Creep on the Performance of a Compressible Inclusion*. Geotextile and Geomembrane, 15(1997), pp.121-131.

New York State Department of Transportation.(1999). *Controlled Low Strength Material (CLSM) Guidelines*, Engineering Instruction (EI) 99-039, December 14, 1999.

Purwito dan Firmanti Anita.(2005). *Pemanfaatan Limbah Sawit dan Asbuton untuk Bahan Pencegah Serangan Rayap Tanah*, Kolokium dan Open Huose, Bandung 8–9 Desember 2005.

Riad, H. L., A. L. Ricci, P. W. Osborn, D. C. Wood and J. S. Horvath. (2003). *Innovative spectrs of the Use of Expanded Polystyrene (EPS) on Boston's 'Big Dig*, preprint paper No. 03-2823, Trans. Res. Bd. 82nd Ann. Mtg., Wash., D.C.

----- . (2004). *Design of Lightweight Fills for Road Embankments on Boston's Central Artery/Tunnel Project*. Massachusetts, Boston., Manhattan College Bronx, New York., U.S. Federal Highway Administration.

Roald Aabøe and Even Øiseth.(2004). *Foamed Glass – An Alternative Lightweight and Insulating Material*, Norwegian Public Roads Authorities, NPRA., SINTEF Civil and Environmental Engineering. Norway.

Tweedie, J.J., Humphrey, D.N., and Sandford, T.C. (1998). *Tire Shreds as Lightweight Retaining Wall Backfill: Active Conditions*. ASCE J. Geotech. and Geoenv. Enrg., Vol. 124, No.11, Nov. 1998, pp.1061-1070.

Artikel:

Judul: *Civil Engineering Aplication*, www.epa.gov/garbage/tires/civil_eng.htm, disunting pada 9 Oktober 2007 pukul 20.00 WIB.

Judul: *Coconut*, <http://en.wikipedia.org/wiki/Coconut>", disunting pada 3 Februari 2008 pukul 20.30 WIB.

Judul: *Granular Coconut Shell Carbon*, TGS Aqua Tech Inc, <http://www.activatecarbon.com>, disunting pada 5 Februari 2008 pukul 19.30 WIB.

Judul: *Mansonville Plastics (BC) Ltd*, www.mansonvilleplastics.com/geof.htm, disunting pada 5 Oktober 2007 pukul 20.00 WIB.

Sumber : Artikel “*Modulus of Soil Reaction (E’)*”, Info Brief. <http://www.rinkermaterials.com/>, disunting pada 5 Mei 2007 pukul 20.00 WIB.